

## Graffiti Eater Long Life Coating

### DESCRIPTION

Graffiti Eater Long Life is a purpose built, clear or coloured UV stable, cross linked, acrylic urethane system for protection of building surfaces against graffiti defacement. Graffiti Eater Long Life is warranted to provide complete graffiti protection for 10 years. Graffiti Eater Long Life also complies with the carbon dioxide test criteria for use as an anti-carbon coating to bridge structures.

Graffiti Eater Long Life forms a clear, long lasting, ultraviolet-resistant film unaffected by weather or any of the solvents commonly used in aerosol paints, leather dyes, texta pens and ball point pens. It is almost impossible to make a permanent mark on a treated surface of Graffiti Eater Long Life, except by deep scratching or gouging. Graffiti Eater Long Life properly applied, will provide protection from graffiti attack for 10 years before recoating becomes necessary.

Graffiti Eater Long Life 's unique chemical composition allows moisture vapour, contained in the building substrate, to be expelled into the atmosphere. Graffiti Eater Long Life is ideal for protection of masonry, brickwork, metal, terracotta, wood, painted surfaces and furniture against defacement in schools, public buildings, toilets and sports pavilions. Graffiti Eater Long Life finds major application where continuous heavy defacement is a problem, such as public toilet walls and doors, bus shelters, lifts and pedestrian underpasses.

### APPLICATION

Application is by approved applicators or qualified painting contractors. Graffiti Eater Long Life should be applied preferably using an airless spray with 5-12 thousand tip size to firm, clean and dry surfaces only. Graffiti Eater Long Life will respond adversely to the presence of contaminants or moisture. Graffiti Eater Long Life may be applied by brush, or airless spray equipment at a spread rate of 6-8 sq meters per litre per coat 40 microns dryfilm build per coat. The solvents used in Graffiti Eater Long Life may affect some types of paint films if brushed on. Spraying gives much more latitude, but check trial section first. Two coats should be applied 24 hours apart. Care must be taken to ensure correct mixing and application is carried out. Graffiti Eater Long Life should **not** be applied if rain is likely within 4 hours of application. Graffiti Eater representatives are available to assist in application techniques. Substrata **MUST** be fully saturated on application or protection will be less than optimum. On application, Graffiti Eater Long Life may give an apparent darkening on certain surfaces by pore-filling effect similar to wetting. Try a small test area first to check if acceptable, also a noticeable gloss may result on some substrates. Graffiti Eater Sacrificial is almost invisible and gloss-free and may be preferred in some circumstances.

Cleaning of equipment must be with Graffiti Eater Coating Thinners only, at least three litres needs to be run through spraying equipment to ensure complete removal of residue.

### REMOVAL OF GRAFFITI FROM

Apply Graffiti Eater All Rounder or Graffiti Eater Masonry graffiti removers by brush. See respective Data Sheets for more information on graffiti removal.

